

## LED CCTV Monitor 42VED Display



### ADVANTAGES

- High Resolution: 1920 x 1080 @60Hz
- Wide Viewing Area (H/V): 178° / 178°
- Clear Contrast Ratio: 1,300:1
- High Brightness: 450 cd/m<sup>2</sup>
- All Metal Cabinet, Eco-Friendly Design
- BNC, S-Video, VGA, Component, HDMI, DVI, Audio, PC Stereo
- Multi Display Function: PIP / PBP / VOV
- 3D Comb Filter, Deinterlacing, Noise Reduction, Trigger Source Switching, Auto Source Sequencing, Auto Power Recovery, Multi Language OSD



VuREX VED series monitors with LED BLU (backlight unit) benefit from intelligent color corrective technology with a mercury-free WLED back-light.

In the long term the LED Monitor will benefit exceptional savings of up to 40% of energy costs.

### SPECIFICATIONS 42VED

<b>Display</b>	Screen Size	42Inch
	Panel Resolution	1920 x 1080 @60Hz
	Pixel Pitch	0.484 x 0.484 mm
	Brightness (Typ.)	450 cd/m <sup>2</sup> (Center,Typ)
	Contrast Ratio	1,300 : 1
	Aspect Ratio	16 : 9
	Viewing Angle (H/V)	178° / 178°
	Display Color	16.7 Million
	Response Time (Gray to Gray)	< 9ms(Typ)
	Video System	NTSC / PAL
<b>Interface</b>	Video In / Out (BNC Type)	2 / 2
	S-Video In	1
	VGA In (15Pin D-Sub)	1
	Component In	1
	HDMI In	2
	DVI In	1
	Audio In (RCA Type)	3(L+R)
PC Stereo In	1	
<b>Transmitter</b>	Remote Control	Yes
<b>Audio</b>	Built-In Speaker	Yes (5W x 2)

Eco-Friendly

<b>Features</b>	Filter Type	3D Comb Filter
	Deinterlacing	Yes
	Noise Reduction	Yes
	Multi Display Function	PIP / PBP (VOV Support)
	Screen Protection	N / A
	Trigger Source Switching	Yes (NC)
	Auto Source Sequencing	Yes
	Auto Power Recovery	Yes
	Multi Language	English, Spanish, French, German, Italian
	<b>Dimension</b>	Outline Dimension (w/o stand) (W x H x D)
Outline Dimension (w/ stand) (W x H x D)		1,020 x 630 x 280 mm
Net. Weight		26Kg
<b>Cabinet</b>	Color / Base Stand	Black / Yes
	Case Material	Metal (Electronic galvanized Iron)
<b>Warranty</b>	Part/Labor	1 year / 1 year
	MTBF (Approx.)	50,000 Hours
<b>Regulations</b>		FCC, CE
<b>Power</b>	Consumption : < On	< 220W
	Electrical Ratings	AC100 ~ 240V(50/60Hz)
<b>Circumstance</b>	Operating Temperature	0~50°C
	Storage Temperature	-20 ~ 60°C
<b>Mount</b>	VESA™ Mount Size	400 x 200 mm
	Mount Kit	Optional (Wall, Rack, Swing Arm, Ceiling)

# LED CCTV Monitor 42VED Display

## OTHER VIEW




REAR VIEW



SIDE VIEW




## DIMENSIONS



▲ FRONT VIEW



▲ SIDE VIEW



▲ REAR VIEW



▲ TOP VIEW

RN Electronics Co., Ltd

Add 414, 172, LS-ro, Gunpo-si, Gyeonggi-do, 435-824, Korea

Tel +82-70-4370-4459 Fax +82-31-624-2130 Email info@vurex.net Website www.vurex.net

**RN**Electronics