

Chassis Frame LCD Monitor 23VIC Display



ADVANTAGES

- Easy integration into custom enclosures or kiosks
- All Metal Case
- VESA Mount Hole (100mm X 100mm)
- Input Signal : VGA, DVI
- Input Power: AC100~240V(50/60Hz), DC 12V/5A
- Touch Screen Options: Resistive, Capacitive, SAW Touch
- 2 year warrnaty

VuREX VIC LCD/LED Chassis Frame Monitors offer easy integration into custom enclosures or kiosks and are ideal as a versatile and long-term display platform for OEM's and designers.

They can be used in both indoor and outdoor environments.

They offer flexible options for touchscreen, signal interface and chassis mounting.

SPECIFICATIONS 23VIC

| | Screen Size | 23" |
|-----------|----------------------|----------------------|
| Display | Max. Resolution | 1366 X 768 @ 60Hz |
| | Panel Type | LCD |
| | Pixel Pitch | 0.124 mm X 0.372 mm |
| | Luminance, White | 450cd/m ² |
| | Contrast Ratio | 800 :1 |
| | Viewing Angle(H/V) | 178°/178° |
| | Support Color | 16.7 Million |
| | Response Time | < 8ms |
| | | |
| | | |
| Interface | VGA In (15Pin D-Sub) | 1 |
| | DVI-D In | 1 |
| | | |
| Audio | Built-In Speaker | N/A |

| Dimension | Outline Dimension (WXHXD) | 590 X 360 X 65mm |
|---------------|---------------------------|-----------------------------------|
| | Net. Weight | TBA |
| | | |
| Cabinet | Cabinet Color | Black |
| | Case Material | Metal(Electronic galvanized Iron) |
| Warranty | Part/ Labor | 2year / 2year |
| MTBF(Approx.) | | 50,000 Hours |
| Regulations | | NRTL, FCC, CE, RoHS |
| Power | Consumption : < On | < 60W |
| | Electrical Ratings | AC110 ~ 230V(50/60Hz) |
| | | DC 24V / 5A |
| Circumstance | Operating Temperature | -30 ℃ to 70 ℃ |
| | Storage Temperature | -20℃ to 80℃ |
| Mount | VESA Size (HXV) | 100mm X 100mm |
| Option | Touch Sensor | Resistive, Capacitive, SAW Touch |

Chassis Frame LCD Monitor 23VIC Display






FRONT VIEW


SIDE VIEW





DIMENSIONS







▲ FRONT VIEW

▲ REAR VIEW

▲ BOTTOM VIEW