

Panel Frame LED Monitor 23VIP Display



ADVANTAGES

- LED Backlight Unit
- Easy integration into custom enclosures or kiosks
- All Metal Case
- VESA Mount Hole (100mm X 100mm)
- Input Signal : VGA, DVI
- Input Power: AC100~240V(50/60Hz), DC 12V / 5A
- Touch Screen Options: Resistive, Capacitive, SAW Touch
- 2 year warrnaty

VuREX VIP LCD/LED Panel Frame Monitors offer easy integration into custom enclosures or kiosks and are ideal as a versatile and long-term display platform for OEM's and designers.

They can be used in both indoor and outdoor environments.

They offer flexible options for touchscreen, signal interface and chassis mounting.

SPECIFICATIONS 23VIPE

Display	Screen Size	23"
	Max. Resolution	1366 X 768 @ 60Hz
	Panel Type	LCD
	Pixel Pitch	0.124 mm X 0.372 mm
	Luminance, White	450cd/m ³
	Contrast Ratio	800 :1
	Viewing Angle(H/V)	178°/178°
	Support Color	16.7 Million
	Response Time	< 8ms
Interface	VGA In (15Pin D-Sub)	1
	DVI-D In	1
Audio	Built-In Speaker	N/A

Dimension	Outline Dimension (WXHXD)	1366 X 768 @ 60Hz
	Net. Weight	TBA
Cabinet	Cabinet Color	Black
	Case Material	Metal(Electronic galvanized Iron)
Warranty	Part/ Labor	2year / 2year
MTBF(Approx.)		50,000 Hours
Regulations		NRTL, FCC, CE, RoHS
Power	Consumption : < On	< 60W
	Electrical Ratings	AC110 ~ 230V(50/60Hz)
		DC 24V / 5A
Circumstance	Operating Temperature	-30℃ to 70℃
	Storage Temperature	-20℃ to 80℃
Mount	VESA Size (HXV)	100mm X 100mm
Option	Touch Sensor	Resistive, Capacitive, SAW Touch

Design and specifications are subject to change without notice

Panel Frame LED Monitor 23VIP Display


OTHER VIEW



FRONT VIEW




REAR VIEW



SIDE VIEW



DIMENSIONS





▲ FRONT VIEW

▲ REAR VIEW

▲ BOTTOM VIEW