

Rack Frame LCD Monitor 15VIR Display



ADVANTAGES

- 15" XGA Color TFT LCD Display
- High Bright TFT LCD: 250cd/m2
- Clear Contrast Ratio: 450 :1
- Heavy Duty Metal Chassis
- Input Signal : VGA, DVI
- Input Power: AC100~240V(50/60Hz), DC 12V / 3.5A
- Standard 19 inch rack mount chassis Dimensions
- Touch Screen: Resistive, Capacitive, SAW Touch
- 2 year warmaty

VuREX VIR Series Rack Mountable LCD Monitors are a rugged, high performance, Active Matrix COLOR TFT LCD monitors designed for all industrial process control applications.

Designed for use in 19" equipment racks, with contrast ratios exceeding 1000:1 and brightness levels of 250cd/m², the VuREX VIR series of Rack mount monitors is a good choice for all of your industrial display needs.

SPECIFICATIONS 15VIR

Display	Screen Size	15"
	Max. Resolution	1024X 768 @ 60Hz
	Panel Type	LCD
	Pixel Pitch	0.297 mm X 0.297 mm
	Luminance, White	250 cd/m²
	Contrast Ratio	450 :1
	Viewing Angle(H/V)	130°/ 100°
	Support Color	16.7 Million
	Response Time	< 5ms
Interface	VGA In (15Pin D-Sub)	1
	DVI-D In	1
Audio	Built-In Speaker	N/A

Dimension	Outline Dimension (WXHXD)	400mm x 290mm x 50mm
	Net. Weight	ТВА
Cabinet	Cabinet Color	Black
	Case Material	Metal(Electronic galvanized Iron
Warranty	Part/ Labor	2year / 2year
MTBF(Approx.)		50,000 Hours
Regulations		NRTL, FCC, CE, RoHSurs
Power	Consumption : < On	< 35W
	Electrical Ratings	AC110 ~ 230V(50/60Hz)
		DC 12V / 3.5A
Circumstance	Operating Temperature	-30℃ to 70℃
	Storage Temperature	-20℃ to 80℃
Mount	VESA Size (HXV)	100mm X 100mm
Option	Touch Sensor	Resistive, Capacitive, SAW Touch


¹ Rack Frame LCD Monitor 15VIR Display


OTHER VIEW





DIMENSIONS







▲ REAR VIEW

▲ BOTTOM VIEW