

## **CCTV Monitor 26VCP Display**



## **ADVANTAGES**

High Resolution: 1920 x 1080 @60Hz
Wide Viewing Area (HAV): 178° / 178°

Wide Viewing Area (H/V): 178° / 178°

• Clear Contrast Ratio: 1,000:1

High Brightness: 400 cd/m²

• All Metal Cabinet, Eco-Friendly Design

 BNC, S-Video, VGA, Component, HDMI, DVI, Audio, PC Stereo

Designed for 24/7 and Panel life: 50,000 hours

 3D Comb Filter, Deinterlacing, Noise Reduction, Trigger Source Switching, Auto Source Sequencing, Auto Power Recovery, Multi Language OSD



**VuREX VCP** Premium Series has various customer-friendly and features with PIP/PBP/VOV, metal cabinets, 3D Comb Filter.

VCP series offers excellent picture quality with a wide viewing angle and a sleek casing that maximises desktop space.

## **SPECIFICATIONS 26VCP**

	Screen Size	26Inch
Display	Panel Resolution	1920 x 1080 @60Hz
	Pixel Pitch	0.3 x 0.3 mm
	Brightness (Typ.)	400cd/m²(Center,Typ)
	Contrast Ratio	1000 : 1
	Aspect Ratio	16 : 9
	Viewing Angle (H/V)	178° / 178°
	Display Color	16.7 Million
	Response Time (Gray to Gray)	< 8ms(Typ)
	Video System	NTSC / PAL
Interface	Video In / Out (BNC Type)	2/2
	S-Video In	1
	VGA In (15Pin D-Sub)	1
	Component In	1
	HDMI In	2
	DVI In	1
	Audio In (RCA Type)	3(L+R)
	PC Stereo In	1
Transmitter	Remote Control	Yes
Audio	Built-In Speaker	Yes (5W x 2)

Features	Filter Type	3D Comb Filter
	Deinterlacing	Yes
	Noise Reduction	Yes
	Multi Display Function	PIP / PBP (VOV Support)
	Screen Protection	Yes
	Trigger Source Switching	Yes (NC)
	Auto Source Sequencing	Yes
	Auto Power Recovery	Yes
	Multi Language	English, Spanish, French, German, Italian
Dimension	Outline Dimension (w/o stand) (W x H x D)	648.8 x 414.2 x 116.5 mm
	Outline Dimension (w/ stand) (W x H x D)	648.8 x 414.2 x 172 mm
	Net. Weight	17kg
Cabinet	Color / Base Stand	Black / Yes
	Case Material	Metal (Electronic galvanized Iron)
Warranty	Part/Labor	2year / 2year
	MTBF (Approx.)	50,000 Hours
Regulations		NRTL, FCC, CE, RoHS
Power	Consumption : < On	< 100W
	Electrical Ratings	AC100 ~ 240V(50/60Hz)
Circumstance	Operating Temperature	0~50°C
	Storage Temperature	-20 ~ 60°C
Mount	VESA™ Mount Size	200 x 200 mm
	Mount Kit	Optional (Wall, Rack, Swing Arm, Ceiling)
		·