

Transparent Monitor 22VTD Display



ADVANTAGES

- Full color display
- Contrast ratio of 500:1 with 1680 x 1050 resolution
- Maximizes convenience by incorporating HDMI
- Corporations and schools can also adopt the panel as an interactive communication device, or for telecommunication
- Touch Screen Options: Resistive, Capacitive, SAW Touch

VuREX VTD Series have a wide range of use in all industry areas as an efficient tool for delivering information and communication.

These panels can be applied to show windows, outdoor billboards, and in showcase events.

SPECIFICATIONS 22VTD

Display	Screen Size	22"
	Max. Resolution	1680 x 1050 @ 60Hz
	Pixel Pitch	0.282 x 0.282mm
	Active Display Area (H x V)	473.76 x 296.1 mm
	Brightness	200 cd/m²
	Contrast Ratio	500 : 1
	Aspect Ratio	16 : 9
	Viewing Angle(H/V)	160° / 140°
	Display Color	16.7 Million
	Response Time	< 5ms
nterface	TMDS (Main) - HDMI	HDMI 1 (TMDS)

	Outline Dimension (W x H)	493.7 x 371 mm
Dimension	Depth	22 mm(T1) / 7.0 mm (T2)
	Net Weight	1.3 Kg
Warranty	Part/ Labor	2year / 2year
	MTBF (Approx.)	50,000 Hours
	Consumption : < On	< 11W
	Electrical Ratings	DC5V / 3A
Circumstance	Operating Temperature	0 ~ 40° C / 32 ~ 122° F
	Storage Temperature	5 ~ 40° C / -22 ~ 176° F

¹ Transparent Monitor 22VTD Display



DIMENSIONS



