

Open Frame LCD Monitor 17VIO Display



ADVANTAGES

- Easy integration into custom enclosures or kiosks
- All Metal Case
- VESA Mount Hole (100mm X 100mm)
- Input Signal : VGA, DVI
- Input Power : AC110~230V(50/60Hz)
- Touch Screen Options: Resistive, Capacitive, SAW Touch
- 2 year warrnaty

VuREX VIO LCD/LED Open Frame Monitors offer easy integration into custom enclosures or kiosks and are ideal as a versatile and long-term display platform for OEM's and designers.

They can be used in both indoor and outdoor environments.

They offer flexible options for touchscreen, signal interface and chassis mounting

SPECIFICATIONS 17VIO

Display	Screen Size	17"
	Max. Resolution	1280 X 1024 @ 60Hz
	Panel Type	LCD
	Pixel Pitch	0.264 mm X 0.264 mm
	Luminance, White	250 cd/m ²
	Contrast Ratio	1,000:1
	Viewing Angle(H/V)	178°/178°
	Support Color	16.7 Million
	Response Time	< 5ms
	VGA In (15Pin D-Sub)	1
	DVI-D In	1
Audio	Built-In Speaker	N/A

Dimension	Outline Dimension (WXHXD)	400 X 340 X 50mm
	Net. Weight	ТВА
Cabinet	Cabinet Color	Silver
	Case Material	Metal(Electronic galvanized Iron)
Warranty	Part/ Labor	2year / 2year
MTBF(Approx.)		50,000 Hours
Regulations		NRTL, FCC, CE, RoHS
Power	Consumption : < On	< 35W
	Electrical Ratings	AC110 ~ 230V(50/60Hz)
		DC 12V / 3.5A
Circumstance	Operating Temperature	-30℃ to 70℃
	Storage Temperature	-20℃ to 80℃
Mount	VESA Size (HXV)	100mm X 100mm
Option	Touch Sensor	Resistive, Capacitive, SAW Touch

¹ Open Frame LCD Monitor 17ViO Display


OTHER VIEW








DIMENSIONS







▲ FRONT VIEW ▲ REAR VIEW

▲ BOTTOM VIEW

