

# Open Frame LCD Monitor 23VIO Display



## **ADVANTAGES**

- Easy integration into custom enclosures or kiosks
- All Metal Case
- VESA Mount Hole (100mm X 100mm)
- Input Signal : VGA, DVI
- Input Power : AC110~230V(50/60Hz)
- Touch Screen Options: Resistive, Capacitive, SAW Touch
- 2 year warrnaty

**VuREX VIO** LCD/LED Open Frame Monitors offer easy integration into custom enclosures or kiosks and are ideal as a versatile and long-term display platform for OEM's and designers.

They can be used in both indoor and outdoor environments.

They offer flexible options for touchscreen, signal interface and chassis mounting

## SPECIFICATIONS 23VIO

Display	Screen Size	23"
	Max. Resolution	1366 X 768 @ 60Hz
	Panel Type	LCD
	Pixel Pitch	0.124 mm X 0.372 mm
	Luminance, White	450cd/m <sup>3</sup>
	Contrast Ratio	800 :1
	Viewing Angle(H/V)	178°/178°
	Support Color	16.7 Million
	Response Time	< 8ms
Interface	VGA In (15Pin D-Sub)	1
	DVI-D In	1
Audio	Built-In Speaker	N/A

Dimension	Outline Dimension (WXHXD)	600 X 370 X 65mm
	Net. Weight	ТВА
Cabinet	Cabinet Color	Silver
	Case Material	Metal(Electronic galvanized Iron)
Warranty	Part/ Labor	2year / 2year
MTBF(Approx.)		50,000 Hours
Regulations		NRTL, FCC, CE, RoHS
Power	Consumption : < On	< 60W
	Electrical Ratings	AC110 ~ 230V(50/60Hz)
		DC 24V / 4.5A
Circumstance	Operating Temperature	-30℃ to 70℃
	Storage Temperature	-20℃ to 80℃
Mount	VESA Size (HXV)	100mm X 100mm
Option	Touch Sensor	Resistive, Capacitive, SAW Touch

# Open Frame LCD Monitor 23VIO Display


#### OTHER VIEW







## **DIMENSIONS**





▲ FRONT VIEW

▲ REAR VIEW

▲ BOTTOM VIEW

