

## Open Frame LCD Monitor 42VIO Display



### **ADVANTAGES**

- High Resolution: 1920 x 1080p Full HD
- Easy integration into custom enclosures or kiosks
- All Metal Case
- VESA Mount Hole (400mm X 200mm)
- Input Signal : VGA, DVI
- Input Power : AC100~240V(50/60Hz)
- Touch Screen Options: IR Touch
- 2 year warrnaty

**VuREX VIO** LCD/LED Open Frame Monitors offer easy integration into custom enclosures or kiosks and are ideal as a versatile and long-term display platform for OEM's and designers.

They can be used in both indoor and outdoor environments.

They offer flexible options for touchscreen, signal interface and chassis mounting

## SPECIFICATIONS 42VIO

Display	Screen Size	42"
	Panel Resolution	1920 X 1080 @ 120Hz
	Panel Type	LCD
	Pixel Pitch	0.4845 mm X 0.4845 mm
	Luminance, White	450 cd/m²
	Contrast Ratio	1,300:1
	Viewing Angle(H/V)	178°/178°
	Support Color	1.06 Billion
	Response Time	< 5ms
Interface	VGA In (15Pin D-Sub)	1
	DVI-D In	1
Audio	Built-In Speaker	N/A

		5
Dimension	Outline Dimension (WXHXD)	1,030 x 630 x 65mm
	Net. Weight	ТВА
Cabinet	Cabinet Color	Silver
	Case Material	Metal(Electronic galvanized Iron)
Warranty	Part/ Labor	2year / 2year
MTBF(Approx.)		50,000 Hours
Regulations		NRTL, FCC, CE, RoHS
Power	Consumption : < On	< 190W
	Electrical Ratings	AC100~240V(50/60Hz)
Circumstance	Operating Temperature	-30℃ to 70℃
	Storage Temperature	-20℃ to 80℃
Mount	VESA Size (HXV)	400mm X 200mm
Option	Touch Sensor	Resistive, Capacitive, SAW Touch

# 1 Open Frame LCD Monitor 42VIO Display


#### OTHER VIEW








## **DIMENSIONS**







▲ FRONT VIEW

▲ REAR VIEW

**▲ BOTTOM VIEW**