

Chassis Frame LCD Monitor 32VIC Display



ADVANTAGES

- Easy integration into custom enclosures or kiosks
- All Metal Case
- VESA Mount Hole (200mm X 200mm)
- Input Signal : VGA, DVI
- Input Power : AC100~240V(50/60Hz)
- Touch Screen Options: IR Touch
- 2 year warrnaty

VuREX VIC LCD/LED Chassis Frame Monitors offer easy integration into custom enclosures or kiosks and are ideal as a versatile and long-term display platform for OEM's and designers.

They can be used in both indoor and outdoor environments.

They offer flexible options for touchscreen, signal interface and chassis mounting.

SPECIFICATIONS 32VIC

Display	Screen Size	32"
	Panel Resolution	1366X 768@ 60Hz
	Panel Type	LCD
	Pixel Pitch	170.25μm X 510.75 μm
	Luminance, White	500 cd/m ³
	Contrast Ratio	800 :1
	Viewing Angle(H/V)	178°/178°
	Support Color	16.7 Million
	Response Time	< 9ms
Interface	VGA In (15Pin D-Sub)	1
	DVI-D In	1
Audio	Built-In Speaker	N/A


Dimension	Outline Dimension (WXHXD)	800mm X 490mm X 80mm
	Net. Weight	TBA
Cabinet	Cabinet Color	Black
	Case Material	Metal(Electronic galvanized Iron)
Warranty	Part/ Labor	2year / 2year
MTBF(Approx.)		50,000 Hours
Regulations		NRTL, FCC, CE, RoHS
Power	Consumption : < On	< 95W
	Electrical Ratings	AC100~240V(50/60Hz)
Circumstance	Operating Temperature	-30℃ to 70℃
	Storage Temperature	-20℃ to 80℃
Mount	VESA Size (HXV)	200mm X 200mm
Option	Touch Sensor	IR Touch


Chassis Frame LCD Monitor 32VIC Display



DIMENSIONS







▲ FRONT VIEW

▲ REAR VIEW

▲ BOTTOM VIEW